Effect of Organic and Inorganic Amendments on Parameters of Water Retention Curve, Bulk Density and Aggregate Diameter of a Saline-sodic Soil

H. Emami¹*, and A. R. Astaraei¹

ABSTRACT

To study the effects of soil amendments on physical and hydraulic properties of a saline-sodic sandy clay loam soil, a field experiment was carried out as a complete block design with three replications. The treatments in this research consisted of control (B), 10 ton ha-1 gypsum (G), 10 ton ha-1 urban solid compost (C), three levels of vinyl alcohol acrylic acid (S1= 0.05%, S2= 0.1%, S3= 0.2%), CS1, CS2, CS3, GS1, GS2, GS3CGS1, CGS2, and CGS3. Four months after applying the treatments, water contents were measured at 9 pressure heads for each treatment and data obtained were fitted to Van Genuchten equation. The parameters of this equation (i.e. θ_s , θ_r , α , and n) were determined by the least square error method. Also some physical properties including bulk density (Bd), mean weight diameter (MWD) of aggregates, plant available water content (PAWC), and the slope of water retention curve at inflection point (S index) were measured. The results showed that all treatments increased saturated water content (θ_s) significantly (P< 0.05) compared with the control (B). A similar trend was observed for residual water content (θ_r). The highest and lowest values of a were noted in B and S2 treatments, respectively. PAWCs increased significantly in all treatments compared with control ones except for G, GS1, GS2, and GS3 treatments (P< 0.05). Adding the soil amendments increased the values of S index and MWD and decreased Bd, significantly compared with the B treatment. It seems that the mixture of vinyl alcohol acrylic acid at 0.1% with urban solid compost or gypsum is a suitable amendment for increasing AWC and improving physical quality of studied salinesodic soils.

Keywords: Gypsum, S index, Soil water retention curve, Urban solid compost.

INTRODUCTION

Unsuitable physical properties of salinesodic soils in arid and semiarid regions restrict root growth and limit plant growth and yield (Karimi and Naderi, 2007). Water holding capacity is important in semiarid and arid regions, where water shortage is very frequent and water is often the main limiting factor in cultivated areas (Andry *et al.*, 2009). Seed germination and plant growth are critically restricted because of low available soil water content and poor soil structure under saline-sodic condition. Therefore, specific soil management is necessary to improve physical properties of these soils. Application of some amendments and alternative irrigation methods are more important, especially in regions with reduced soil water availability (Abedi-Koupai *et al.*, 2008).

In most soils, organic matter is applied as a soil conditioner for increasing water holding capacity and improving soil physical properties. Hammer *et al.* (2011) compared the effect of different organic matter sources and inorganic nutrient supply and an improved soil water holding capacity via

1625

¹ Department of Soil Science, College of Agriculture, Ferdowsi University of Mashhad, Mashhad, Islamic Republic of Iran.

^{*} Corresponding author; e-mail: hemami@um.ac.ir

application of hydrophilic polymers. The strongest effect was caused by organic matter. Karhu et al. (2011) applied biochar to boreal agricultural soil and found that water holding capacity increased by 11%. Rawls et al. (2003) reported increasing organic matter content led to an increase of water retention in sandy soils, and to a decrease in fine-textured soils. At high organic carbon values, all soils showed an increase in water retention. The largest increase was in sandy and silty soils (Rawls et al., 2013). Ouattara et al. (2006) found that organic matter input improved field capacity and soil water content at wilting point.

hydrophilic In modern agriculture, polymers are used to enhance both the nutritional and water status of plants (Andry et al., 2009). There are reports that hydrophilic polymers are capable of retaining water up to 400-1,500 times of their weight (Johnson, 1984a; Bowman and Evans, 1991; Buchholz, 1998). These polymers can build an additional water reservoir for plant-soil system (e.g. Bouranis et al., 1995) and therefore reduce water stress in plants. The performance of such amendments depends on their chemistry, formation, polymer and chemical composition of the soil solution or irrigation water. Flannery and Busscher (1982) and Johnson (1984a) reported that the use of hydrophilic polymers increased the amount of available soil moisture in the root zone, thus permitting longer intervals between irrigations. Hydrophilic polymers are effective in increasing water holding decreasing deep percolation. capacity. reducing evaporation losses in sandy soils (Teyel and El-Hady, 1981; El-Shafei et al., 1992), improving aeration and drainage of soil medium (Bearce and McCollum, 1977), improving market life of container grown plants (Eikhof et al., 1994; Still, 1976; Bearce and McCollum, 1977), and seed coating (Pamuk, 2004). Eventually, the use of hydrophilic polymers leads to an increase in water holding capacity, since water that would have otherwise leached beyond the root zone is captured.

Soil amendments influence infiltration rates, bulk density, structure, compaction, aggregate stability and crust hardness (Helalia and Letey, 1988; Helalia and Letey, 1989). Gehring and Lewis (1980) reported that moisture stress of plants decreased by the incorporation of a super absorbent into the medium. Silberbush et al. (1993a) tested the polyacrylamide (PAM) hydrophilic gel Agrosoak (0, 0.15, 0.30, and 0.45% by weight in the upper 25 cm of soil) as a conditioner for corn (Zea mays L.) and indicated that soil water storage capacity increased with the rate of Agrosoak. Crop yield components, except shoot dry weight, also increased with the Agrosoak application rate. Furthermore, Silberbush et al. (1993b) investigated the effect of Agrosoak hydrogel on cabbage (Brassica oleraceae L.) and reported that it increased water availability which indeed contributed to the increase in crop yield after irrigation with saline water.

Johnson (1984b) mixed sand with different cross-linked polyacrylamides to produce a polymer concentration range of 0-2 g kg⁻¹ and reported that all polymer treatments increased the field capacity (FC) of coarse sand from 171 to 402%. Also, Johnson (1984b) showed that the permanent wilting point (PWP) of control sand was reached between 2–3 days, in comparison with 1 g kg⁻¹ polymer treated sand (6–7 days) and 2 g kg⁻¹ polymer treated sand (9–10 days).

Abedi-Koupai *et al.* (2008) examined the effect of PR3005A and Tarawat A100 hydrogels on water retention characteristic curves of three sandy loam, loamy, and clay soil textures. Their results showed that the θ_s values were 2.2, 1.8, and 1.5 times the control values of sandy loam, loam, and clay loam soil textures, respectively. Also the θ_r values were 5, 3.3, and 2.2 times the control in sandy loam, loam, and clay soils, respectively. Abedi-Koupai *et al.* (2008) found that adding and increasing the amount of hydrogel on sandy loam reduced α (empirical curve fitting parameter and related to the inverse of air entry value

suction), while the required pressure for water release was increased. But in clayey and loamy soils, the air entry value decreased, i.e., α was increased. They also concluded that incorporation of hydrogels may release water at low matric suctions particularly for clay soil texture and application of 8 g kg⁻¹ of hydrogel addition in sandy loam soil enhanced available water content approximately 3fold compared to that of the control. Thus, the application of hydrogels can result in significant reduction in the required irrigation frequency, which is an important issue in arid and semi-arid regions of the world (Abedi-Koupai et al., 2008).

Andry et al. (2009) evaluated the effects polymers, of two hydrophilic carboxymethylcellulose (RF)and isopropylacrylamide (BF) on the water holding capacity and saturated hydraulic conductivity (K_s) of a sandy soil and found that the soil-absorbent mixtures retained significantly (P < 0.05) more water than the control soil, and the water content increased with increasing amount of hydrophilic polymer in the soil. The increase in mixing ratio from 0.1 to 0.2% did have a significant effect (P < 0.05) on *PAWC*.

Dexter (2004) showed that the slope of water retention curve at the inflection point can reflect different aspects of soil quality such as infiltration, hard-setting, compaction, organic contents, matter aeration, and root growth, etc. He defined the slope of retention curve as a soil physical quality index (S index). S index is an estimation of soil micro-structure and can be measured easily from retention curve.

Quantifying flow and transport in the vadoze zone requires knowledge of the retention and conductivity functions (Haverkamp *et al.*, 2005). Fitting the soil moisture retention curve to a mathematical function such as Van Genuchten and then calculating S index or quantifying flow and transport in terms of the parameters of function is more convenient. Here we focus on the description of the soil moisture retention curve.

Plants grown on hydrophilic polymers amended soil were slower to wilt than those grown on non amended soil (Woodhouse and Johnson, 1991). In addition, the effects of hydrophilic polymers on water retention curve were investigated by Abedi-Koupai et al. (2008) and Andry et al. (2009). However, the individual and interaction effects of hydrophilic polymers, urban solid compost, and gypsum on water retention curve, plant available water and especially S index were not studied in saline-sodic soils. The aim of the present research was to study the effects of hydrophilic polymers, urban solid compost, gypsum, and mixture of amendments with hydrophilic polymers on soil water retention curve, MWD, and Bulk density in a saline-sodic sandy clay loam.

MATERIALS AND METHODS

Site Description

The studied area is located in the eastern part of Shahrood region of Semnan Province in Iran (36° 31 12.18" N, 55° 54 43.86" E). The average annual air temperature and precipitation at the studied site are 16°C and 124.7 mm, respectively. The studied soil was a saline-sodic soil with sandy clay loam texture. Winter wheat (*Triticum aestivum*) and barley (*Hordeum vulgare*) are cultivated in the studied area. Sampling was carried out in the root zone (0-25 cm depth) in April 2010 and some chemical and physical properties were determined (Table 1).

A field experiment was executed to study the effects of organic (urban solid compost) and inorganic (gypsum) amendments, vinyl alcohol acrylic acid and a mixture of former and latter with hydrophilic polymers on structural and hydraulic properties of a saline-sodic sandy clay loam soil in a randomized complete block design with three replications. Size of plots was 1.5×1.5 m, with 1 m distance between plots. The treatments consisted of 10 ton ha⁻¹ gypsum (G), 10 ton ha⁻¹ urban solid compost (C), three levels of vinyl alcohol acrylic acid

Textur e	Sand (%)	Silt (%)	Clay (%)	TNV^a (%)	OC^b (%)	SAR ^c	pН	EC^d (dS m ⁻¹)
		(USDA)						
SCL^e	61	16	23	16.4	0.29	28.7	8.11	25.6

Table 1. Physical and chemical properties of the studied soil before applying the treatments.

^{*a*} Calcium Carbonate; ^{*b*} Organic Carbon; ^{*c*} Sodium Absorption Ratio; ^{*d*} Electrical Conductivity, ^{*e*} Sandy Clay Loam.

 $(S_1 = 0.05\%, S_2 = 0.1\%, S_3 = 0.2\%)$, a mixture of urban solid compost (10 ton ha⁻¹) with each level of vinyl alcohol acrylic acid (CS₁, CS_2, CS_3), a mixture of gypsum (10 ton ha⁻¹) with each level of vinyl alcohol acrylic acid (GS_1, GS_2, GS_3) , a mixture of gypsum (10) ton ha⁻¹) and urban solid compost (10 ton ha⁻ ¹) with each level of vinyl alcohol acrylic acid (CGS₁, CGS₂, CGS₃) and one control (untreated soil (B)). Soil amendments were mixed by hand with 0-15 cm of soil in each experimental plot, Sorghum (Pegah cultivar) was grown and irrigated during the experiment in 5 day intervals. Four months after sowing of plants and establishing the experiment, soil sampling was performed as undisturbed (by cores of 5 cm diameter and 5 cm height) from the surface layer (ranging from 5 to 10 cm) of the center of each plot.

Laboratory Analysis

Some chemical properties of soil samples were analyzed after air drying and passing through a 2-mm sieve. Soil texture was determined using the hydrometer method (Gee and Bauder, 1986). Organic carbon (OC) content in soil was determined by dichromate oxidation procedure (Nelson and Sommers, 1982). Total CaCO₃ equivalent (CCE) was measured by estimating the quantity of the CO₂ produced by HCl addition to the soil (Nelson, 1982). pH was measured in a 1:2.5 soil to water suspension using a pH meter (Mc Lean, 1982). Flame photometry was used for soluble Na⁺, and titrations with ethylenediaminetetraacetic acid (EDTA) were conducted for soluble Ca²⁺ and Mg²⁺. Soil electrical conductivity (EC_e) was measured in saturated paste extract and sodium adsorption ratio (SAR) was calculated as (SAR= $Na^+/[(Ca^{2+}+Mg^{2+})/2]^{0.5}$, where Na^+ , Ca^{2+} , and Mg^{2+} are the ionic concentrations in soil solution (mmol L⁻¹).

Soil core samples were used to measure bulk density and moisture retention curve. Gravimetric water content was measured at 0, 10, 30, 50, 100, 300, 500, 1,000 and 1,500 kPa pressure heads by pressure plate (Klute, 1986). Data of moisture retention curve were fitted to the Van Genuchten equation (1980). The parameters of this equation were determined by the least square error method. The Van Genuchten equation (1980) for soil moisture retention curve is:

$$\theta = \theta_r + \left(\theta_s - \theta_r\right) \left[1 + \frac{1}{\left(\alpha h\right)^n}\right]^{-m}$$
(1)

S index, which is the slope of soil moisture retention curve at the inflection point, in all treated soil samples was calculated as follows (Dexter, 2004):

$$S = -n\left(\theta_{s} - \theta_{r}\left[1 + \frac{1}{m}\right]^{-(1+m)}$$
(2)

If m=1-1/n is applied:

$$S = -n\left(\theta_{s} - \theta_{r}\right)\left[\frac{2n-1}{n-1}\right]^{\left\lfloor\frac{1}{n}-2\right\rfloor}$$
(3)

Where, *n* and α are empirical parameters, and θ_s and θ_r are saturated and residual water contents (g g⁻¹), respectively. Since S index is always negative, the modulus of S index was used in this paper. An example of a soil moisture retention curve and S index is shown in Figure 1. Plant available water content *PAWC* ($m^3 m^{-3}$) was defined according to White (2006) as:

 $PAWC = \theta_{FC} \quad (h = -10 \quad kPa) - \theta_{PWP} \quad (h = -1500 \quad kPa)$ (3)

Mean weight diameter (MWD) was determined by wet sieving method as an index of soil aggregation. The wet sieving method of Kemper and Rosenau (1986) was used with a set of sieves of 4, 2, 1.5, 1, 0.5and 0.25 mm mesh diameters. After treated soil samples were passed through an 8 mm sieve, approximately 50 g of soil was placed on the first sieve of the set, and gently moistened from below to avoid a sudden rupture of aggregates. Once the soil had been saturated, the set was oscillated in distilled water at the rate of 30 oscillations per hour for 10 min. The soil retained in each sieve was dried. The mean weight diameter was calculated as follows:

$$MWD = \sum_{i=1}^{n} X_i W_i \tag{4}$$

Where, *MWD* is the mean weight diameter of water-stable aggregates (mm), X_i is the mean diameter of each size fraction (mm) and W_i is the weight proportion of the total sample mass in the corresponding size fraction after the mass of stones were subtracted from mass retained on each sieve.

Bulk density was determined by core samples of 98.13 cm^3 volume (5 cm in diameter, and 5 cm in height) (Blake and

Hartge, 1986).

Statistical Analyses

The statistical analysis was performed using MSTAT-C software and treatment means were compared using Duncan's multiple range test (DMRT) at P < 0.05.

RESULTS AND DISCUSSION

Parameters of Moisture Retention Curve

Results showed that for all treatments θ_s increased significantly (P< 0.05) compared to the control (Table 2). The increase in θ_s may be due to the positive effect of soil amendments used (i.e. C, S, and G) on aggregation, improvement of soil structure, and consequently increasing soil porosity. S_1 treatment had the highest θ_s , with 90.7% increase compared to the control (B) (untreated soil), followed by CGS_2 , CS_3 , CS₂, and CS₁ treatments. Despite significant increases in θ_s of G, GS₁, GS₂, GS₃, and S₃ treatments with respect to the control, the lowest increment of θ_s was observed in these treatments. Apparently, a period of four months was not enough for full chemical reactions of gypsum in soil and some



Figure 1. Example of a soil moisture retention curve and its slope at the inflection point (from Dexter, 2004).

Treatments	$\theta_{\rm s} ({\rm g}{\rm g}^{-1})$	$\theta_r (g g^{-1})$	α parameter	<i>n</i> parameter	PAWC	S Index	MWD	Bd
			(cm^{-1})		$(g.g^{-1})$		(mm)	$(g.cm^{-3})$
В	0.21 ^g	0.0^{i}	0.0301 ^b	1.183 ^e	0.11^{f}	0.024 ^g	1.94 ^g	1.56 ^a
G	0.281^{f}	0.0^{i}	0.0392 ^a	1.2 ^e	0.11^{f}	0.035^{f}	2.66 ^d	1.24 ^{de}
С	0.35^{bcd}	0.039 ^e	0.02433 ^c	1.286 ^{bcd}	0.151 ^{bc}	0.050^{bcd}	2.17^{f}	1.14^{f}
S_1	0.40^{a}	0.039 ^e	0.0107 ^h	1.346 ^{ab}	0.15 ^{bc}	0.066^{a}	1.92 ^g	1.33 ^c
S_2	0.30 ^{ef}	0.040 ^e	0.0102^{h}	1.352 ^{ab}	0.14^{bcd}	0.048^{bcde}	1.94 ^g	1.40^{b}
S_3	0.29^{f}	0.059 ^a	0.01097^{h}	1.406 ^a	0.13^{bcd}	0.048^{bcde}	1.99 ^g	1.41 ^b
\mathbf{GS}_1	0.28^{f}	0.0^{i}	0.02237^{d}	1.228 ^{cde}	0.12 ^{ef}	0.038^{ef}	2.78 ^c	1.25 ^{de}
GS_2	0.291^{f}	0.0^{i}	0.01697 ^e	1.231 ^{cde}	0.13^{bcd}	0.040^{cdef}	2.90^{ab}	1.25 ^{de}
GS_3	0.296^{f}	0.0^{i}	0.0151^{fg}	1.218 ^{de}	0.11^{f}	0.039 ^{def}	2.99 ^a	1.22 ^{de}
CS_1	0.359 ^{bc}	0.044 ^d	0.01393 ^g	1.308 ^{bc}	0.17 ^a	0.053 ^b	2.23 ^f	1.21 ^e
CS_2	0.361 ^{bc}	0.049 ^c	0.01337 ^g	1.305 ^{bc}	0.16 ^{ab}	0.052^{b}	2.5 ^e	1.33 ^c
CS_3	0.365 ^b	0.054^{b}	0.01153 ^h	1.310 ^{bc}	0.13 ^{bcd}	0.053 ^b	2.93 ^{ab}	1.28 ^{cd}
CGS_1	0.326 ^{de}	0.028 ^g	0.0167 ^{ef}	1.300 ^{bcd}	0.15 ^{bc}	0.049^{bcde}	2.80°	1.26 ^{de}
CGS_2	0.386^{ab}	0.039 ^e	0.01603 ^{ef}	1.355 ^{ab}	0.15^{bc}	0.064^{a}	2.91^{ab}	1.40^{b}
CGS_3	0.331 ^{cd}	0.035^{f}	0.01583 ^{ef}	1.319 ^b	0.16 ^{ab}	0.051 ^{bc}	2.87 ^{bc}	1.28 ^{cd}

Table 2. The effects of studied treatments on soil water retention curve parameters, MWD, and Bd in a saline-sodic sandy clay loam soil.

 θ_s : Saturated water content; θ_r : Residual water content; α and n: Empirical parameters of soil water retention curve; AWC: Plant available water content; MWD: Mean weight diameter of aggregates, Bd: Bulk density. * Means with same letter in each column are not significantly different at 5% probability level.

reactions of gypsum might have influenced the optimum operation of the absorbent in the mixture of soil-gypsum-absorbent system. In general, increasing levels of vinyl alcohol acrylic acid did not further increase θ_s .

Results showed that the changes of θ_r were similar to those of θ_s . The values of θ_r obtained from Van Genuchten equation (1980) were zero in control, G, GS_1 , GS_2 , and GS₃ treatments, but the application of absorbent (S), C, and their mixtures increased θ_r significantly (P< 0.05) and S₃ treatment had the highest θ_r (Table 2). Although gypsum application improved chemical properties of the studied salinesodic soils and decreased exchangeable sodium percentage (i.e. initial and final ESP were 33 and 22% respectively, indicating 15% reduction of ESP in G treatment), its effect on soil moisture retention at high suctions was not noticeable after a period of four months.

Results also indicated that treatments affected the α parameter of Van Genuchten equation (1980). The highest values of α were noted in G and control treatments and their differences (P< 0.05) compared to each other and also to other treatments were significant (Table 2). $1/\alpha$ reflects the air entry value. Thus, the pressures required for water to be released in G and control were 25.5 and 3.32 kPa, respectively. Due to increasing content of macro-pores in G treatment, the α value was increased and water was released under lower matric suction. The lowest α values were found in S₂, S₁, S₃, and CS₃ treatments. Therefore, by applying different levels of the absorbent, air entry values were increased significantly (P< (0.05) compared to the control. For example, the air entry value in S_2 was 98 cm H_2O . The α value was reduced in all treatments (except G treatment), consequently the pressure for water to be released increased (Table 2).

The shape parameter of moisture retention curve (n) in most treatments increased significantly compared to the control (P<0.05). In G, GS₁, GS₂, and GS₃ treatments, the *n* parameter showed no significant differences compared to the control. S₃ treatment had the highest *n* value (Table 2). Soil amendments such as absorbent (S), C and their mixture in this study changed pore size distribution as well as affected moisture retention and/or release of soil moisture, thereby changing the retention curve shape and n parameter value. Plant available water content (PAWC)

Urban solid compost (C) and absorbent (S) application increased plant available water content (Table 2) significantly (P < 0.05). PAWC increased significantly in all treatments compared with the control except for G, GS_1 , GS_2 , and GS_3 treatments (P< 0.05). Maximum amount of PAWC was obtained in CS_1 with an increase of 70% compared to the control. Since C and especially absorbent have a good capacity for water absorption, organic matter can be considered as the best amendment for most soils due to its increase in water retention physical and properties capacity improvement of soils (Karimi and Naderi, 2007). Andry et al. (2009) reported the effects of two hydrophilic polymers, carboxymethylcellulose (RF) and isopropyl acrylamide (BF), on water holding capacity and saturated hydraulic conductivity (K_s) of a sandy soil and found that the available water content increased up to 4 and 5 times with RF and BF treatments, respectively, compared with the control soil.

Many studies that used absorbents in sandy soils reported that the absorbents' efficiency values were higher than those obtained in this study. The soil texture used in this study was sandy clay loam. Therefore, despite leading to an increase in *PAWC*, its increase was lower than those reported by other authors (e.g. Abedi-Koupai *et al.*, 2008; Andry *et al.*, 2009). However, water uptake and plants growth in saline-sodic soils are more restricted than non-saline or non-sodic soils, especially in

arid and semi-arid regions such as the studied area. Minimum and maximum significant increments of PAWC were 30% in S_2 and 70% in CS_3 , respectively. It has been reported that the impact of hydrogel polymers decreases by increasing salinity (Taylor and Halfacre, 1986; Chen et al., 2004; Seved Dorraji et al., 2010). The studied soil in this research was a salinesodic soil and therefore, the maximum values of super absorbent did not have a noticeable impact on PAWC. The studied soil is located in an arid region and sodicity and salinity are the main limiting factors for water uptake and plant growth in this area. Therefore, 70% increment of PAWC can help increase water uptake by plant, promote nutrient uptake, and improve plant growth and crop yield.

Slope of Moisture Retention Curve at Inflection Point (S Index)

The results showed that the lowest S index was found for the control (Table 2). According to Dexter (2004) and Reynolds et al. (2009), our soil structure is classified as poor. Soil SAR and organic carbon are 28.7 and 0.29 %, respectively (Table 1), indicating that the studied soil has a poor structure due to lower organic carbon content and higher amount of soluble and exchangeable Na⁺. Application of soil amendments to this poor soil not only resulted in a significant increase in S index compared to the control, but also improved soil physical quality. S index in all treatments increased at least up to 0.035 (compared to the control) (Table 2). For temperate and tropical soils, $S \ge 0.050$ indicates "very good" soil physical or structural quality, while $0.035 \le S \le$ 0.050 is "good physical quality", $0.020 \le S \le$ 0.035 is "poor physical quality", and $S \le 0.020$ is "very poor" or "degraded" physical quality (Dexter, 2004; Dexter and Czyz, 2007; Tormena et al., 2008; Reynolds et al., 2009). The theoretical limits of S are $0 \le S \le \infty$, however, agricultural soils tend to fall within the range of $0.007 \le S \le 0.14$ (Dexter and Czyz, 2007). The values of S index for C, CS_1 , CS_2 , S_1 , CGS₂, and CGS₃ treatments were equal to (C) and beyond 0.050. Therefore, the amendments employed in this study proved their superiority in improving the soil physical or structural quality of the saline- sodic soil, and they can help to improve root development and plant growth.

Mean Weight Diameter of Aggregates (MWD)

Application of amendments resulted in an increase in MWD (Table 2). However, different levels of absorbent had no significant effect on MWD. In contrast, the mixture of C, gypsum and absorbent increased MWD significantly (P< 0.05) compared with the control. Among different treatments, the highest value of MWD was noted in GS₃, CS₃, CGS_2 and GS_2 treatments. It seems that Ca^{++} in gypsum effectively substituted Na⁺ at exchange sites in the studied saline-sodic soil, acted as bonding agent among soil particles and improved the MWD of aggregates. The results of MWD showed that, except for S treatments which were not significant compared with B, the increasing percentage of MWD for other treatments varied in the range of 12 to 54.5%. Some authors reported that soil amendments can improve soil structure through the increase in MWD. For example, Levy and Miller (1999) found that adding a polyacrylamide to two different soils (Typic Ochraquults, and Typic Hapludults) increased MWD in both soils.

Bulk Density (Bd)

Application of amendments resulted in a significant decrease in Bd (P< 0.05). The lowest Bd was obtained for C treatment being 37% smaller than the one for the control. Mixtures of C with absorbent and gypsum with absorbent treatments also showed significant reductions in Bd compared with the control (P< 0.05). In spite of the significant differences in Bd among different levels of absorbent compared with

the control, the decrease in Bd in absorbent treatments was comparatively smaller than those for the treatments with C, G, and their mixture with absorbent (Table 2). The application of gypsum and urban solid compost resulted in aggregation, soil structure improvement, soil porosity increase, and macro-pores formation in the studied saline-sodic soil and consequently bulk density decrease, and as a result an increase in θ_s was observed.

CONCLUSIONS

The effect of organic and inorganic amendments (urban solid compost, gypsum and vinyl alcohol acrylic acid) on the Van Genuchten retention curve parameters (θ_s , θ_r , n, α), plant available water (PAWC) and soil physical properties mean weight diameter (MWD) and bulk density (Bd) showed that the application of amendments resulted in a significant increase in θ_s , θ_r , and *PAWC*, but a decrease in α parameter. Application of gypsum had no effect on moisture retention at high matric suctions (θ_r) . It seems that gypsum can increase the content of macropores and as a result, θ_s . The studied soil was saline-sodic with low organic carbon content and poor physical and structural quality. All treatments lead to S index increase up to the critical limit (0.035) of soil physical quality with a significant (P< 0.05) difference compared with the control. In addition, the application of amendments decreased Bd, but MWD was increased significantly (P< 0.05). Furthermore, Na⁺ content and electrical conductivity are high in the studied soil. Therefore, soil moisture retention which increases plant available water content and soil physical and structural quality are important factors for plant growth in this area. Our results show that the mixture of 0.1% (g g⁻¹) of vinyl alcohol acrylic acid with C or gypsum seems to be a suitable amendment for the retention of moisture, supplying more plant available water content, and improving soil physical and structural quality. Because supplying more *PAWC* is very important in arid and semiarid regions, increasing soil quality up to the 0.050 value, and decreasing Bd are important as well. Therefore, the mixture of 0.1% vinyl alcohol acrylic acid and 10 ton ha⁻¹ urban solid compost, i.e. CS_1 , was found to be the best amendment among the studied treatments for increasing *PAWC* and improving physical quality of the studied saline-sodic soil.

REFERENCES

- Abedi-Koupai, J., Sohrab, F. and Swarbrick, G. 2008. Evaluation of Hydrogel Application on Soil Water Retention Characteristics. J. Plant Nutr., 31: 317–331.
- Andry, A., Yamamoto, T., Irie, T., Moritani, S., Inoue, M. and Fujiyama, H. 2009. Water Retention, Hydraulic Conductivity of Hydrophilic Polymers in Sandy Soil as Affected Temperature and Water Quality. J. Hydr., 373: 177-183.
- 3. Bearce, B. C. and McCollum, R. W. 1977. A Comparison of Peatlite and Noncomposted Hardwood-bark Mixes for Use in Pot and Bedding-plant Production. Effects of a New Hydrogel Soil Amendment on Their Performance. *Flor. Rev.*, **161(66):** 21–23.
- Blake, G. R. and Hartge, K. H. 1986. Bulk Density. Part1. Physical and Mineralogical Methods. In: "*Methods of Soil Analysis*", (Ed.): Klute, A.. Seconds Edition, Agronomy No.9, *America Society of Agronomy*, Inc. Soil Science Society of America, Madison, Wisconsin, USA, PP.363-373.
- Bouranis, D. L., Theodoropoulus, A. G. and Drossopoulus, J. B. 1995. Designing Synthetic Polymers as Soil Conditioners. *Commun. Soil Sci. Plant Anal.* 26:1455– 1480.
- Bowman, D. C. and Evans, R. Y. 1991. Calcium Inhibition of Poly Acryl Amide Gel Hydration is Partially Reversible by Potassium. *Hort. Sci.*, 26(8):1063–1065.
- Buchhloz, F. L. 1998. The Structure and Properties of Super-absorbent Poly Acrylates. In: "Modern Super-absorbent Polymer Technology", (Eds.): Buchhloz, F. L. and Graham, A. T. Wiley-VCH, New York, PP. 167-221.

 Chen, S. H., Zommorodi, M., Fritz, E., Wang, S. H. and Huttermann, A. 2004. Hydrogel Modified Uptake of Salt Ions and Calcium in *Populus euphratica* under Saline Conditions. *Trees*, 18: 175-183.

JAST

- 9. Dexter, A. R. 2004. Soil Physical Quality. Part I. Theory, Effects of Soil Texture, Density, and Organic Matter, and Effects on Root Growth. *Geoderma*, **120**: 201-214.
- 10. Dexter, A. R. and Czyz, E. A. 2007. Applications of *S*-theory in the Study of Soil Physical Degradation and Its Consequences. *Land Degrad. Develop.* **18**: 369–381.
- Eikhof, R. H., King, P. A. and Koven, G. 1994. Control of Wilting in Potted Plants. *Ohio Flor. Assoc. Bul.* 532:6-7.
- El-Shafei, Y. Z., Al-Omran, A. M., Al-Darby, A. M. and Shalaby, A. A. 1992. Influence of upper Layer Treatment of Gelconditioner on Water Movement in Sandy Soils under Sprinkler Infiltration. *Arid Soil Res. Rehab.*, 6: 217-231.
- Flannery, R. L. and Busscher, W. J. 1982. Use of Synthetic Polymer in Potting Soils to Improve Water Holding Capacity. *Commun. Soil Sci. Plant Anal.* 13: 103-111.
- 14. Gee, G. W. and Bauder, J. W. 1986. Particle–size Analysis. Part 1- Physical and Mineralogical Methods. In: "*Methods of Soil Analysis*", (Ed.): Klute, A.. Second Edition, Agronomy No.9, *America Society of Agronomy*, Inc. Soil Science Society of America, Madison, Wisconsin, USA, PP.381-411.
- 15. Gehring, J. M. and Lewis, A. L. 1980. Effect of Hydrogel on Wilting and Moisture Stress of Bedding Plants. J. A. S. Hort. Sci., **105(4)**: 511-513.
- Hammer E. C., Nasr, H. and Wallander, H. 2011. Effects of Different Organic Materials and Mineral Nutrients on Arbuscular Mycorrhizal Fungal Growth in a Mediterranean Saline Dryland. *Soil Biol. Bioch.*, 43: 2332-2337.
- Haverkamp, R., Leij, F. J., Fuentes, C., Sciortino, A. and Ross, P. J. 2005. Soil Water Retention. I. Introduction of a Shape Index. *Soil Sci. Soc. A. J.*, **69**: 1881–1890.
- Helalia, A. and Letey, J. 1988. Cationic Polymer Effects on Infiltration Rates with a Rainfall Simulator. *Soil Sci. Soc. A. J.*, **52**: 247–250.
- 19. Helalia, A. M. and Letey, J. 1989. Effects of Different Polymers on Seedling Emergence,

1633

Aggregate Stability and Crust Hardness. *Soil Sci.*, **148(3):** 199–203.

- Johnson, M. S. 1984a. Effect of Soluble Salts on Water Absorption by Gel-forming Soil Conditioners. J. Sci. Food Agr., 35: 1063–1066.
- Johnson, S. J. 1984b. The Effects of Gelforming Poly Acryl Amides on Moisture Storage in Sandy Soils. *J. Sci. Food Agr.*, 35:1196–1200.
- Karhu, K., Mattila, T. Bergström, I. and Regina, K. 2011. Biochar Addition to Agricultural Soil Increased CH₄ Uptake and Water Holding Capacity: Results from a Short-term Pilot Field Study. *Agr. Ecosys. Envir.*, **140**: 309-313.
- 23. Karimi, A. and Naderi, M. 2007. Yield and Water Use Efficiency of Forage Corn as Influenced by Superabsorbent Polymer Application in Soils with Different Textures. *Agr. Res. J.*(Iran). **7(3):**187-198.
- Kemper, W. D. and Rosenau, R. C. 1986. Aggregate Stability and Size Distribution. Part Z. Physical and Mineralogical Methods. In: "*Methods of Soil Analysis*", (Ed.): Klute, A.. Agronomy Monograph No.9, *American Society of Agronomy*, Soil Science Society of America, Madison, WI, USA, PP. 425-442.
- Klute, A. 1986. Water Retention: Laboratory Methods. Part 1. Physical and Mineralogical Methods. In: "Methods of Soil Analysis", (Ed.): Klute, A.. Seconds edition. Agronomy No.9. America Society of Agronomy, Inc. Soil Science Society of America, Madison, Wisconsin. USA.
- 26. Levy, G. J. and Miller, W. P. 1999. Poly Acryl Amide Adsorption and Aggregate Stability. *Soil Till. Res.*, **51**:121-128.
- Mc Lean, E. O. 1982. Soil pH and Lime Requirement, Part 2. Chemical and Microbiological Properties. In: "*Methods of Soil Analysis*", (Eds.): Page, A. L., Miller, R. H., and Keeney, D. R.. 2nd Edition, Agronomy Monograph No. 9, ASA and SSSA, Madison, WI, PP. 199–224.
- Nelson, D. W. and Sommers, L. E. 1982. Total Carbon, Organic Carbon, and Organic Matter. Part 2. Chemical and Microbiological Properties. In: "*Methods of Soil Analysis*", (Eds.): Page, A. L., Miller, R. H., and Keeney, D. R.. 2nd Edition, Agronomy Monograph No. 9, ASA and SSSA, Madison, WI, PP. 539–580.

- Nelson, R. E. 1982. Carbonate and Gypsum. In: Part 2. Chemical and Microbiological Properties. In: "*Methods of Soil Analysis*", (Eds.): Page, A. L., Miller, R. H., and Keeney, D. R.. 2nd Edition, Agronomy Monograph No. 9. ASA and SSSA, Madison, WI, PP. 188–192.
- Ouattara, K., Ouattara, B., Assa, A. and Sédogo, P. M. 2006. Long-term Effect of Ploughing and Organic Matter input on Soil Moisture Characteristics of a Ferric Lixisol in Burkina Faso. *Soil Till. Res.*, 88: 217-224.
- 31. Pamuk, G. S. 2004. Controlling Water Dynamics in Scots Pine (*Pinus sylvestris* L.) Seeds before and during Seedling Emergence. PhD. dissertation. Department of Silviculture Umea, Swedish University of Agricultural Sciences.
- Rawls, W. J., Pachepsky, Y. A., Ritchie, J. C., Sobecki, T. M. and Bloodworth, H. 2003. Effect of Soil Organic Carbon on Soil Water Retention. *Geoderma*, **116**: 61-76.
- 33. Reynolds, W. D., Drury, C. F., Tan, C. S., Fox, C. A. and Yang, X. M. 2009. Use of Indicators and Pore Volume-function Characteristics to Quantify Soil Physical Quality. *Geoderma*, **152**: 252-263.
- 34. Seyed Dorraji, S., Golchin, A. and Ahmadi, S. 2010. The Effects of Different Levels of a Super Absorbent Polymer and Soil Salinity on Water Holding Capacity with Three Textures of Sandy, Loamy and Clay. J. Water Soil, (Iran). 24(2): 306-316.
- Silberbush, M., Adar, E. and De Malach, Y. 1993a. Use of a Hydrophilic Polymer to Improve Water Storage and Availability to Crops Grown in Sand Dune. I. Corn Irrigated by Trickling. *Agri. Water Manag.*, 23(4): 303–313.
- 36. Silberbush, M., Adar, E. and DeMalach, Y. 1993b. Use of an Hydrophilic Polymer to Improve Water Storage and Availability to Crops Grown in Sand Dune Cabbage Irrigated by Sprinkling with Different Water Salinities. Agri. Water Manag, 23(4): 315– 327.
- 37. Still, S. M. 1976. Growth of Sunny Mandalay Chrysanthemums in Hard Wood Bark Amended Medium as Afected by Unsolubilized Polyethylene Oxides. *Hort. Sci.*, **11(5)**: 483–484.
- Taylor, K. C. and Halfacre, R. G. 1986. The Effect of Hydrophilic Polymer on Media Water Retention and Nutrient Availability to

Ligustrum lucidum. Hort. Sci., **21**: 1159-1161.

- Teyel, M. Y. and El-Hady, O. A. 1981. Super Gel as a Soil Conditioner. *Acta Hort.*, 119: 247-256.
- 40. Tormena, C. A., Da Silva, A. P., Imhoff, S. D. C. and Dexter, A. R. 2008. Quantification of the Soil Physical Quality of a Tropical Oxisols Using the *S* Index. *Sci. Agric.*, **65**: 56–60.
- Van Genuchten, M. Th. 1980. A Closedform Equation for Predicting the Hydraulic Conductivity of Unsaturated Soils. *Soil Sci. Soc. Am. J.*, 44: 892–898.
- White, R. E. 2006. Principles and Practice of Soil Science. 4th Edition, Blackwell Publishing, Oxford, UK. P. 363.
- Woodhouse, J. and Johnson, M. S. 1991. Effect of Super-absorbent Polymers on Survival and Growth of Crop Seedlings. *Agri. Water Manag.*, 20: 63–70.

تاثیر اصلاح کنندههای آلی و غیرآلی بر پارامترهای منحنی رطوبتی، جرم مخصوص ظاهری و میانگین وزنی قطر خاکدانهها در یک خاک شور-سدیمی

ح. امامي، و ع. ر آستارايي

چکیدہ

جهت مطالعه تاثیر مواد بهساز بر ویژگیهای هیدرولیکی و فیزیکی خاک، آزمایشی در قالب طرح بلوكهاي كامل تصادفي با سه تكرار در يك خاك شور – سديمي با بافت لوم رسي شني انجام شد. تيمارهاي اين تحقيق شامل تيمار شاهد (B)، ١٠ تن در هكتار يودر گچ (G)، ١٠ تن در هكتار كميوست زباله شهري (C)، ماده سویر جاذب وینیل اکریلیک اسید در سه سطح (./۰۵، = s₁= ۰/۰۱، S₁= ۰/۰۱ و /۲/۰ =(S₁)، CGS₂, CGS₁, GS₂, GS₂, GS₁, CS₃, CS₂, CS₁)، دند. بعد از گذشت ۴ ماه از اعمال تیمارها، رطویت تیمارهای مختلف در نه مکش اندازه گیری شدند و دادههای به دست آمده با معادله وان گناختن برازش داده شدند. سیس با استفاده از روش حداقل مربعات خطا، یارامترهای (b_s) n و n) معادله مذکور تعیین شدند. همچنین بعضی از ویژگیهای فیزیکی خاک مثل جرم مخصوص (n معادله مذکور تعیین شدند. ظاهري (Bd)، ميانگين وزني قطر خاكدانهها (MWD)، رطوبت قابل استفاده گياه (PAWC) و شيب منحنی رطوبتی در نقطه عطف آن (شاخص S) نیز اندازه گیری شدند. نتایج نشان دادند که تمام تیمارهای آزمایشی رطوبت اشباع خاک $(heta_{
m s})$ را به طور معنی داری نسبت به تیمار شاهد افزایش دادند lpha). روند تقریبا مشابهی در مورد رطوبت باقی مانده ($heta_{
m r}$) نیز مشاهد شد، بیشترین مقدار (P < 0.05) مربوط به تیمار شاهد و کمترین مقدار یارامتر مذکور نیز متعلق به تیمار S₂ بود. غیر از تیمارهای G، GS₂ ،GS₁ و GS₃ در بقیه تیمارها رطوبت قابل استفاده گیاه بهطور معنی داری نسبت به شاهد افزایش نشان داد (P< 0.05). افزودن مواد بهساز به خاک به طور معنی داری شاخص S و مقادیر MWD را افزایش و Bd را نسبت به شاهد کاهش داد. به نظر می رسد ترکیب ۰/۱ درصد وینیل اکریلیک اسید با ۱۰ تن در هکتار کمپوست زباله شهری و گچ، اصلاح کننده مناسبی برای افزایش AWC و بهبود کیفیت فیزیکی در خاک شور–سدیمی باشد.